

EER Cores (9598283402)



Part Number: 9598283402

98 EER CORE SET

EER cores, similar to ETD cores, have been designed to make optimum use of a given volume of ferrite material for maximum throughput power. The structure, which includes a round center post, approaches a nearly uniform cross-sectional area throughout the core and provides a winding area that minimizes winding losses.

EER cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 32 (g)

| _ | <u>ı.</u> 32 (g | <u>, </u> | | | |
|---------------------------|-----------------|--|--------------|-------------------|--|
| Dim | mm | mm tol | nominal inch | inch misc. | |
| A | 28.5 | ± 0.60 | 1.122 | _ | |
| В | 16.9 | ± 0.20 | 0.665 | _ | Chart Legend Σl/ A : Core Constant, l _e : Effective Path Length, A _e : Effective Cross- Sectional Area, V _e Effective Core Volume |
| C | 11.4 | ± 0.30 | 0.449 | _ | |
| D | 12.5 | ± 0.20 | 0.492 | _ | |
| Е | 21.2 | min | 0.835 | min | |
| F | 9.9 | ± 0.30 | 0.39 | _ | |
| A _L : Expla | | tance Facto of Part Num | | = product class a | nd 3 & 4 = material grade. |

| Electrical Properties | | | | | |
|-----------------------|-----------|--|--|--|--|
| $A_L(nH)$ | 2710 ±25% | | | | |
| Ae(cm ²) | 0.852 | | | | |
| $\Sigma l/A(cm^{-1})$ | 8.7 | | | | |
| l _e (cm) | 7.44 | | | | |
| $V_e(cm^3)$ | 6.337 | | | | |
| $A_{min}(cm^2)$ | 0.77 | | | | |

A, value is measured at 1 kHz, B < 10 gauss.

Fair- Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288

888-324-7748

845-895-2055

Fax: 845-895-2629

ferrites@fair- rite.com •

www.fair- rite.com