





		I		2		3		4	
[PRODUCT NUMBER						I		
	51939-812								
	NOTE: 3								
	NOTES:								
		NSIONS AND TOLERANCE YI4.5M, 1994 UNLESS							
	CONNECT	DR NOTES:							
		ING MATERIAL: UL 94	V-0 CLASS EL	LIED HIGH TEMP T					
	\bigcirc	ER CONTACT MATERIAL:			HERMOFLASTIC				
	SIG	NAL PIN MATERIAL: CO	PPER ALLOY						
	3. SEE	TEM I & 2 IN PRINT	10064183 FOR	PLATING SPEC OF	51939-812 AND 519	39-812LF RESPECTIVELY	•		
	(4.) MANU	FACTURER'S NAME, DA	TE CODE AND O	PTIONAL P/N TO A	PPEAR ON				
	THIS SPAC	SURFACE. THE MARK C ON THIS SURFACE.	CAN BE OMITTEE	D IF THERE IS NO	T ENOUGH				
	5. PROD	JCT SPECIFICATION GS	5-12-149.						
		ICATION SPECIFICATIO)N BUS-20-067.						
		AGED IN TRAYS.							
	PCB N								
	7. ALL	HOLE DIAMETERS ARE F	INISHED HOLE	SIZE.					
	(8.) MOUN	TING HOLES, WHERE AF	PPLICABLE, AR	E UNPLATED.					
	\bigcirc	I5I±0.025 DRILLED H⊄ D8 MIN SnPb OR Sn OV		(IIH					
	ΤO	0.08 Cu PLATING TO A 02±0.07 HOLE.							
	\sim								
	(10.) CONN	ECTOR KEEP-OUT ZONE							
				dr Ruan MT	2013/09/26	projectio		s i z e	scale
				eng Ruan MT	2013/10/10		MM	A 4	1:1
				chr -	-			ecn no	-
				appr Pei-Ming Zheng	2013/10/10	product fami		ade rel level	Released
				FCì	$\frac{1}{2}$ 4ACP +	9DCP + 32S		5 939-8	2 rev
					· —	E SOLDER HEADER	م * 9	21323 01	Δ Α
				www.fci.com			Product - Cust	2	heet 4 of 4

Ĩ