
HellermannTyton

Specification Sheet

Part Number: 558-00216



Article Number	558-00216
Туре	TAG20-47W508SM
Color	White (WH)
Features & Benefits	• HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing. • Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time. • Labels are UL recognized for indoor and outdoor use to expand application options. • HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.
Quantity Per	roll

_				_					
-	rn	ИI	ıct	11	20	cri	n	ы	nη
	··	uu	101	$\boldsymbol{\nu}$	63	UI I		ч	vii

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Short Description	SwiftMark Self-Laminating Label, 2.0" x .5" x 1.0", VL, White, 4500/roll
Global Part Name	TAG20-47W508SM-100B-WH
Technical Description	SwiftMark Self-Laminating Label, 2.0" X .5" X 1.0", White
Variant	Roller form
Width W (Imperial)	2.0
Width W (Metric)	50.8
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.6
Bundle Diameter Max (Imperial)	0.2
Bundle Diameter Max (Metric)	5.08
Thickness T (Metric)	25
Height H (Imperial)	0.5

Height H (Metric)	12.70
Width of Liner (Metric)	53.97
Width of Liner (imperial)	2.125
Outside Diameter Max(Imperial)	0.18
Outside Diameter Min (metric)	2.0
Outside Diameter Min(Imperial)	0.078
Outside Diameter Max (metric)	4.7
Material	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
Material Material Shortcut	Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating
Material Shortcut	100B
Material Shortcut Adhesive	100B Acrylic
Material Shortcut Adhesive Adhesive Operating Temperature	100B Acrylic -40°F to +194°F (-40°C to +90°C)
Material Shortcut Adhesive Adhesive Operating Temperature Operating Temperature (Metric)	100B Acrylic -40°F to +194°F (-40°C to +90°C) -51°F to +200°F (-46°C to +93°C)
Material Shortcut Adhesive Adhesive Operating Temperature Operating Temperature (Metric)	100B Acrylic -40°F to +194°F (-40°C to +90°C) -51°F to +200°F (-46°C to +93°C)

Customs Number	3919102055
Labels per Row	1
Weight (Metric)	2.04
Weight (Imperial)	4.5

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@}$ 2018 HellermannTyton. All rights reserved.