



Isometric View



- REFERENCE:  
 PERFORMANCE REQUIREMENTS AT DRY AS MOLDED:
1. FIR TREE PUSH IN FORCE: REF. 10 LBS MAX IN A 6.6mm HOLE AND A PLATE THICKNESS OF 1.8mm
  2. FIR TREE PULL OUT FORCE: REF. 30 LBS MIN IN A 6.6mm HOLE AND A PLATE THICKNESS OF 1.8mm
  3. SHEET METAL THICKNESS RANGE: 0.70mm - 5.75mm

INVENTORS

**HellermannTyton**<sup>®</sup>

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER SHOWN ON THIS DRAWING ARE EXCLUSIVE PROPERTY OF HELLERMANN TYTON

name	date	city, state
S. ADAMS	9/29/07	MENOMONEE FALLS, WI.

REVISIONS

REV	level	DATE	BY	ECN #	part level
02		2/17/08	SJA	010955	A

DIMENSIONS

TOLERANCES	units
.XXXX = ± 0.25	millimeters
.XXX = ± 0.50	
.XX = ± 1.00	
.X = ± 2.00	
∠ = ± 0.50	
unless otherwise specified	

PART

number	phase
SOC7FT6	PRODUCTION
name	
TAPE CLIP WITH OFFSET (31mm) AND FIR TREE (6.6mm)	
material	
NYLON 6/6, IMPACT MODIFIED, HEAT STABILIZED, UV RESISTANT COLOR: BLACK	

DRAWING

FORMAT	AH	CAD	CATIA V5	SCALE
VERSION	J			1:1
A- SIZE (landscape)_N01		previous drawing number		
drawn	checked	approved		
S. ADAMS	J. PASSILLA			
9/29/07	9/29/07			
type		sheet 1 of 1		
CUSTOMER				
number	MT07-028-004CST			