	2									1					
	THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USE										'AY DETRIME	NTAL TO THE	INTERESTS (DF PANDUIT CORP.	
			_	\\\/\	RE RANGE	IGE			DIMENSIONS in. [mm]	WIRE STRIP LENGTH	T00LS		
	PANDUIT PART #			VVI	AWG [mm²]	TAB SIZE in. [mm]	HOUSING COLOR	MAX WIRE INSUL DIA	L ± .04 [1,1]	W ± .01 [0,3]	M ± .02	in. [mm] +1/32 [0,8] -0			
		EDV18-1	187MB		#22-16 [0.5-1.5]		RED	0.145 [3.7]	0.75 [19.0]	0.19 [4.8]	.39 [10.0]	9/32	KST2000C		
		EDV14-	187MB		#16-14 [1.5-2.5]		BLUE	0.165 [4.2]	0.75 [19.0]	0.19 [4.8]	.39 [10.0]	[6.8]	K312000C		
B														- SERRATED BARREL	B
	NOTES: 1. UL LISTED FOR: A. STRANDED COPPER WIRE ONLY - INTERNAL WIRING B. 167°F (75°C) MAX TEMP RATING C. 300V MAX VOLTAGE RATING								/IRING	W				MAX WIRI INSUL D	
2. MATERIAL: A. STAMPING: .016" [0.4] THICK BRASS, TIN PLATED B. HOUSING: VINYL STAMPING													→		
	3. SEE www.panduit.com FOR PACKAGE QUANTITIES													- HOUSING	
7	4. DIMENSIONS IN BRACKETS ARE METRIC EQUIVAL														
								LISTED 19X5 E78522	IS			L		-	
											TITLE		LE DISCOM	NECTO (107 CEDIEC)	
A											STRONGHOLD MALE DISCONNECTS (187 SERIES) VINYL INSULATED #22-14 AWG				
											CUSTOMER DRAWING ITEM REVISION NAME 00123SSN/00				
											DATASET FILE NAME			P ANDUIT	
											UNLESS DIMENSIONA	OTHERWISE SPE L TOLERANCES A	CIFIED.	MATERIAL:	
											.x ± .1 [.xx ± .01		_	SEE NOTES	
00DA/12	00	2/18	JHNU	TMR	RGB	DRAWING RELEASED				00123SS		PF PF	IRD ANGLE ROJECTION	DRAWING NUMBER: 0012355N - DC	
010100	REV	DATE	ВҮ	CHK	APR		DESCRI	PTION		ECN	JHNU DATE	- RLS	N.T.S.	I I	A
	2									1					